

Platinum

| | |
|------------------------------------|---|
| CoxOrb | |
| Size | 105mm/4 1/8" diameter, 90mm/3.5" deep |
| Weight | 0.49kg/1lb 1.5oz |
| Display | High contrast, sunlight readable, backlight LCD display with automatic light level control |
| Controls | Six outer edge buttons (start/stop,split/clr,time,mute,recall and display). Two separate volume control buttons |
| Mouldings | Front Bumper: Injection moulded elastomeric polymer Back Bumper: Injection moulded elastomeric polymer Main Unit: Toughened Acrylic Battery Pack: Polycarbonate Speakers: PC/ABS alloy |
| GPS | 10 Hz, 66 channel |
| Speed/Split | Can be displayed as either Speed (meters per second) or Split (time for 500 meters). GPS speed smoothed over 0-8 strokes (user adjustable) and can be Stream Compensated. Impeller Speed smoothed over 2 strokes |
| Stroke Rate | 10-55 per minute, rate input from accelerometer or seat magnet |
| Timing | 0-99:59.59 (minutes:seconds) |
| Stroke Count | 0-99 |
| Memory | 2GB memory stores data every stroke (time/rate/check/speed/distance/distance per stroke),as applicable. Audio recording stores microphone voice input during timed pieces |
| Distance | Meters |
| Check Factor | Derived from averaging the boat decelerations during each stroke |
| Compliance & Durability | |
| Waterproof | IP67, NEMA-6 |
| Impact | Will survive repeated drops onto concrete from 1.5m/4ft |
| EMC | Fully tested and compliant |
| Buoyancy | Unit with battery pack installed and microphone attached floats, unit alone floats, microphone does not float |
| Battery Pack | |
| Specification | 17Wh 1600mAh removable battery pack |
| Life | 5-6 hours of normal use (50% volume, 50% talking) |
| Charging Time | 3 hours with 1000mA charger |